Verito: A Practical System for Transparency and Accountability in Virtual Economies (Don't count your credits before they are cashed)

Raghav Bhaskar, Saikat Guha, Srivatsan Laxman, **Prasad Naldurg Microsoft Research India**



Virtual economies


Encash (d, credits) = money



Purchase (u, money) = credits











Spend (u,d,credits)











All credits are not worth the same


- Value of credits
 - "Facebook has in the past issued a small amount of Credits at no cost to certain users (for example, a new user of Credits, or someone whose usage has lapsed). If you receive those Credits in transactions, we will not redeem them."
 - Promotions by Facebook and Advertisers (cost borne by FB and advertisers; see image)
- Credits in different currencies
 - Arbitrage



Lack of Transparency

- Platform pays out different amounts of cash for same # of credits
 - Developers cannot do fine-grained accounting
 - Rely on trust, regulation
- Not very popular
 - FB does not do free credits any more
 - Cost of differentiation passed on to developers
 - Linden \$ and Bitcoin have private exchanges
 - You get what somebody else thinks you are worth
 - MS points were withdrawn as they were priced differently in different currencies
 - Arbitrage

Requirements wishlist



Solution: first cut

- Credits are just value-signature pairs
 - Transparency
 - Security




- Performance
 - Double spending





- A practical, efficient, secure credits system for transparency and fairness in virtual economies
- Design: Credit(q,k)
 - Credit is a commitment on a nominal value
 - q: security parameter, k: buckets (aggregation level)





Solution Overview

Platforms
"accumulates" &
checks spent/
encashed credits



Platform "commits" value of credit



Developers







Developers see commitments only in aggregate


User can see committed value



- Homomorphic commitments
- Dynamic Accumulators

- Compare/contrast with ecash
 - Anonymity, unlinkability
- Anonymous credentials

Commitment schemes



Homomorphic: Commit (m1)*Commit(m2)=Commit(m1+m2)

Homomorphic Commitment Scheme [Pedersens]

- Commitment on m is $c = g^r h^m$; Note $c_1 * c_2 = g^{r1} h^{m1} * g^{r2} h^{m2} = g^{r1+r2} h^{m1+m2}$
- User gets to see c, m and r and thus can check correctness of all its credits
- Developer gets only c and cannot infer anything about m
- Ouring Encash, Platform reveals $\sum r_i$ and $\sum m_i$ to the Developer who can check it against the product of credits ($\prod c_i$) that it submitted

Dynamic Accumulators



- "Hash" a large set of input values to a single short value
- Check for value is (not) in accumulator using a "witness"
- Infeasible to find witness for a value not in accumulator
 - Typically used for efficient (credential) revocation
 - WE DON'T USE ZERO KNOWLEDGE
- Dynamic Accumulators
 - Addition, deletion efficient, independent of accumulator values
 - Used to check double spending, double encashment

AccGen(1k): Generate accumulator

Inputs: c1, c2, c3,
Outputs: α, w1, w2, w3

AccAdd (c_k, α)
Output: α' , wit_k

AccWitUpdate(wit_k')
No secrets needed

AccVerify(value, witness)

- = 1 if value in α , using witness
- = 0 otherwise

Dynamic Accumulators [ATSM09, ...]

- lacktriangle
- Note δ is secret per accumulator, known only to the Platform
- For a set $\{c_1, ..., c_m\}$, the accumulating value $V = P_1^{\prod_{i=1}^m (\delta + c_i)}$
- For a credit c in the set, $\left(W=P_1^{\prod_{i=1}^m(\delta+c_i)/(\delta+c)},Q=VW^{-c}\right)$ is the witness that c is accumulated in V
- When a new c' is accumulated, the new witness of c can be computed as $(W' = VW^{(c'-c)}, Q' = V'W'^{-c})$, where V' is the new accumulating value

Putting it all together



 $\sum m, \sum r$





 $\{g^rh^m, E_K(r,m)\}, r, m, (w,q)\}$

 $egin{array}{l} acc_u = 1 & acc_{m{q}} & E^{\gamma} \dot{\mathbf{T}}^{g^r h^m} \ acc_u = P^{(\delta + g^r h^m)} \end{array}$

 $w_u, w_d, auth$

Purchase

Encash





 w_d , auth







 $\{g^rh^m, E_K(r,m)\}$

Spend

Properties: Transparency



- Adversary wins attack game if Platform can produce m1' <> m1 and CheckCredit(c1, m1') is true.
- Similarly merchant transparency



- Adversary wins if D can correctly return r' = // with prob > 1/2
- Other properties: double spending and encashment follow similarly

Fairness: Issues

- Merchant can attribute credit characteristics to users after encash
 - Policy: Enforce minimum number of tokens for each encash
 - Cannot resend credits across multiple encash transactions, as they are "used" up

Properties: Summary

Accountability: User transparency	Binding property of Pedersen's commitments	DLOG assumption	
Accountability: Merchant transparency	Binding + homomorphic property of Pedersen's commitments	DLOG assumption	
Security: Double spending	Dynamic accumulator scheme (both spending and encashment)	DDH and q-strong DH assumption	
Security: Non repudiation	Signatures	Signature assumptions	
Fairness	Hiding property of Pedersen's commitments	Information-theoretic	

Flexibility (multiple currencies) and arbitrage prevention by design

Implementation and Deployment


Performance


Efficient

- Purchase (around 830 credits/sec, crypto dominates)
- Spend /Encash (2X faster than purchase) for batches of 100
 - Verify most expensive
 - Witness updates can be batched

Feasible

- Can generate around 71 million credits a day (26 B a year, around 100 B required)
- Can be incrementally deployed on FB





Success! Game purchased!

36

Settings

▲ Games



















Conclusions

	MS Points (W)	FB Credits (C)	Linden \$\$	Bitcoin	Verito
Security	\checkmark	V	\checkmark	?	
Transparency	Fixed	?	Fluctuates	Fluctuates	
Flexibility	Tied to USD	Tied to USD	Tied to exchange	Tied to exchange	
Fairness		?			
Performance				Expensive	

- Transparency and Fairness are vital requirements in a virtual economy
 - Collusions?
 - Simpler? More efficient?